



South Coast AQMD
Site Survey Report for Los Angeles (Central)-North Main Street

Last updated May, 2014



AQS ID	ARB Number	Site Start Date	Reporting Agency and Agency Code
060371103	70087	09/1979	South Coast AQMD (061)

Site Address	County	Air Basin	Latitude	Longitude	Elevation
1630 North Main Street Los Angeles, CA 90012	Los Angeles	South Coast	34° 03' 59"N	118° 13' 36"W	89



Detailed Site Information

Local site name	Los Angeles-North Main Street			
AQS ID	060371103			
GPS coordinates (decimal degrees)	Latitude: 34° 03' 59" Longitude: 118° 13' 36"			
Street Address	1630 North Main Street, Los Angeles, CA 90012			
County	Los Angeles			
Distance to roadways (meters)	51 - 71			
Traffic count (AADT, year)	15,276 / 2012			
Groundcover (e.g. asphalt, dirt, sand)	Asphalt			
Representative statistical area name (i.e. MSA, CBSA, other)	31080-Los Angeles, Long Beach-Anaheim MSA			
Pollutant, POC	Carbon Monoxide, 1	Nitrogen Dioxide, 1	Ozone, 1	Sulfur Dioxide, 9
Parameter code	42101	42602	44201	42401
Basic monitoring objective(s)	NAAQS	NAAQS	NAAQS	NAAQS
Site type(s)	Population Exposure	Highest Concentration	Population Exposure	Population Exposure
Monitor (type)	SLAMS\PAMS/ NCore	SLAMS\PAMS/ NCore	SLAMS\PAMS/ NCore	SLAMS\NCore
Instrument manufacturer and model	Horiba 370	Thermo 42i	API/Teledyne 400E	Thermo 43i-TLE
Method code	158	074	087	560
FRM/FEM/ARM/ other	FRM	FRM	FEM	FEM
Collecting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Analytical Lab (i.e. weigh lab, toxics lab, other)	N/A	N/A	N/A	N/A
Reporting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Spatial scale (e.g. micro, neighborhood)	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Monitoring start date (MM/DD/YYYY)	09/1979	09/1979	09/1979	09/1979
Current sampling frequency (e.g. 1:3, continuous)	1:1	1:1	1:1	1:1
Calculated sampling frequency (e.g. 1:3/1:1)	N/A	N/A	N/A	N/A
Sampling season (MM/DD-MM/DD)	01/01-12/31	01/01-12/31	01/01-12/31	01/01-12/31
Probe height (meters)	12.3	12.3	12.3	12.3
Distance from supporting structure (meters)	2.0	2.0	2.0	2.0
Distance from obstructions on roof (meters)	N/A	N/A	N/A	N/A
Distance from obstructions not on roof (meters)	N/A	N/A	N/A	N/A

Distance from trees (meters)	N/A	N/A	N/A	N/A
Distance to furnace or incinerator flue (meters)	45	45	45	45
Distance between collocated monitors (meters)	N/A	N/A	N/A	N/A
Unrestricted airflow (degrees)	360°	360°	360°	360°
Probe material for reactive gases (e.g. Pyrex, stainless steel, Teflon)	Teflon	Teflon	Teflon	Teflon
Residence time for reactive gases (seconds)	.8	1.2	1.7	3.1
Will there be changes within the next 18 months? (Y/N)	No	No	No	No
Is it suitable for comparison against the annual PM2.5? (Y/N)	N/A	N/A	N/A	N/A
Frequency of flow rate verification for manual PM samplers	N/A	N/A	N/A	N/A
Frequency of flow rate verification for automated PM analyzers	N/A	N/A	N/A	N/A
Frequency of one-point QC check for gaseous instruments	Nightly	Nightly	Nightly	Nightly
Last Annual Performance Evaluation for gaseous parameters (MM/DD/YYYY)	07/13/2013	07/13/2013	07/13/2013	07/13/2013
Last two semi-annual flow rate audits for PM monitors (MM/DD/YYYY, MM/DD/YYYY)	N/A	N/A	N/A	N/A

Pollutant, POC	PM10, 2	PM10, 4	Lead, 3	Lead, 2
Parameter code	See Table 26	See Table 26	14129	14129
Basic monitoring objective(s)	NAAQS	NAAQS	NAAQS	NAAQS
Site type(s)	Population Exposure	Population Exposure	Population Exposure	Population Exposure

Monitor (type)	SLAMS/NATTS/ NCore	SLAMS/NATTS/ NCore/QA Collocated	SLAMS/Pb/QA Collocated	SLAMS/Pb
Instrument manufacturer and model	GMW 1200 SSI, A Sampler	GMW 1200 SSI, B Sampler	GMW 1200 TSP, B Sampler	GMW 1200 TSP, A Sampler
Method code	063, 102	063, 102	110	110
FRM/FEM/ARM/ other	FRM	FRM	FRM	FRM
Collecting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Analytical Lab (i.e. weigh lab, toxics lab, other)	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Reporting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Spatial scale (e.g. micro, neighborhood)	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Monitoring start date (MM/DD/YYYY)	01/1985	01/2007	09/1979	09/1979
Current sampling frequency (e.g. 1:3, continuous)	1:6	6 per Year	1:6	1:6
Calculated sampling frequency (e.g. 1:3/1:1)	1:6	6 per Year	1:12	1:6
Sampling season (MM/DD-MM/DD)	01/01-12/31	01/01-12/31	01/01-12/31	01/01-12/31
Probe height (meters)	11.7	11.7	11.3	11.3
Distance from supporting structure (meters)	1.5	1.5	1.1	1.1
Distance from obstructions on roof (meters)	N/A	N/A	N/A	N/A
Distance from obstructions not on roof (meters)	N/A	N/A	N/A	N/A
Distance from trees (meters)	N/A	N/A	N/A	N/A
Distance to furnace or incinerator flue (meters)	27	27	27	27
Distance between collocated monitors (meters)	2	2	2	2
Unrestricted airflow (degrees)	360°	360°	360°	360°
Probe material for reactive gases (e.g. Pyrex, stainless steel, Teflon)	N/A	N/A	N/A	N/A
Residence time for reactive gases (seconds)	N/A	N/A	N/A	N/A
Will there be changes within the next 18 months? (Y/N)	No	No	No	No

Is it suitable for comparison against the annual PM2.5? (Y/N)	N/A	N/A	N/A	N/A
Frequency of flow rate verification for manual PM samplers	Monthly	Monthly	Monthly	Monthly
Frequency of flow rate verification for automated PM analyzers	N/A	N/A	N/A	N/A
Frequency of one-point QC check for gaseous instruments	N/A	N/A	N/A	
Last Annual Performance Evaluation for gaseous parameters (MM/DD/YYYY)	N/A	N/A	N/A	N/A
Last two semi-annual flow rate audits for PM monitors (MM/DD/YYYY, MM/DD/YYYY)	06/28/2013, 12/20/2013	06/28/2013, 12/20/2013	12/20/2013, 06/28/2013	12/20/2013, 06/28/2013

Pollutant, POC	Continuous PM10, PM Coarse, 9	Continuous PM2.5, PM Coarse, 9	Speciated PM2.5, 11	Speciated PM2.5, 12
Parameter code	85101	88101	See Table 26	See Table 26
Basic monitoring objective(s)	NAAQS	NAAQS	NAAQS	NAAQS
Site type(s)	Population Exposure	Highest Concentration	Highest Concentration	Highest Concentration
Monitor (type)	SLAMS/NCore	SLAMS/NCore	SLAMS	SLAMS/QA Collocated
Instrument manufacturer and model	Met One BAM 1020	Met One BAM 1020	Met One SASS, A Sampler	Met One SASS, B Sampler
Method code	122	170	See Table 26	See Table 26
FRM/FEM/ARM/ other	FEM	FEM	Other	Other
Collecting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Analytical Lab (i.e. weigh lab, toxics lab, other)	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Reporting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Spatial scale (e.g. micro, neighborhood)	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Monitoring start date (MM/DD/YYYY)	11/04/2010	03/08/2011	03/2001	03/2001
Current sampling frequency (e.g. 1:3,	1:1	1:1	1:6	1:6

continuous)				
Calculated sampling frequency (e.g. 1:3/1:1)	N/A	N/A	No CFR mandated sampling schedule.	No CFR mandated sampling schedule.
Sampling season (MM/DD-MM/DD)	01/01-12/31	01/01-12/31	01/01-12/31	01/01-12/31
Probe height (meters)	12.0	12.8	12.0	12.0
Distance from supporting structure (meters)	1.8	2.6	1.8	1.8
Distance from obstructions on roof (meters)	N/A	N/A	N/A	N/A
Distance from obstructions not on roof (meters)	N/A	N/A	N/A	N/A
Distance from trees (meters)	N/A	N/A	N/A	N/A
Distance to furnace or incinerator flue (meters)	51	51	51	51
Distance between collocated monitors (meters)	4	4	2	2
Unrestricted airflow (degrees)	360°	360°	360°	360°
Probe material for reactive gases (e.g. Pyrex, stainless steel, Teflon)	N/A	N/A	N/A	N/A
Residence time for reactive gases (seconds)	N/A	N/A	N/A	N/A
Will there be changes within the next 18 months? (Y/N)	No	No	No	No
Is it suitable for comparison against the annual PM _{2.5} ? (Y/N)	N/A	No, unless the manual sampler has missing data.	N/A	N/A
Frequency of flow rate verification for manual PM samplers	N/A	N/A	Monthly	Monthly
Frequency of flow rate verification for automated PM analyzers	Monthly	Monthly	N/A	N/A
Frequency of one-point QC check for gaseous instruments	N/A	N/A	N/A	N/A
Last Annual Performance Evaluation for gaseous parameters (MM/DD/YYYY)	N/A	N/A	N/A	N/A

Last two semi-annual flow rate audits for PM monitors (MM/DD/YYYY, MM/DD/YYYY)	06/28/2013, 12/14/2013	06/28/2013, 12/14/2013	06/28/2013, 12/14/2013	06/28/2013, 12/14/2013
--	------------------------	------------------------	------------------------	------------------------

Pollutant, POC	24 Hour PM2.5, 1	24 Hour PM2.5, 2	24 Hour VOCs, 2	3 Hour VOCs, 1
Parameter code	See Table 26	See Table 26	See Table 26	See Table 26
Basic monitoring objective(s)	NAAQS	NAAQS	NAAQS	NAAQS
Site type(s)	Highest Concentration	Highest Concentration	Highest Concentration	Highest Concentration
Monitor (type)	SLAMS	SLAMS/QA Collocated	Research Support/NATTS	Research Support/PAMS
Instrument manufacturer and model	Andersen RAAS PM2.5, A Sampler	Andersen RAAS PM2.5, B Sampler	Xontech 910A, A Sampler	Xontech 910A, B Sampler
Method code	780, 120	780, 120	See Table 26	See Table 26
FRM/FEM/ARM/other	FRM	FRM	Other	Other
Collecting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Analytical Lab (i.e. weigh lab, toxics lab, other)	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Reporting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Spatial scale (e.g. micro, neighborhood)	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Monitoring start date (MM/DD/YYYY)	01/1999	01/1999	01/2007	01/2007
Current sampling frequency (e.g. 1:3, continuous)	1:1	1:6	1:6	1:1 during Intensive PAMS Season
Calculated sampling frequency (e.g. 1:3/1:1)	1:3	1:6	No CFR mandated sampling schedule.	No CFR mandated sampling schedule.
Sampling season (MM/DD-MM/DD)	01/01-12/31	01/01-12/31	01/01-12/31	07/01-09/30
Probe height (meters)	12.1	12.1	12.6	12.6
Distance from supporting structure (meters)	1	1	1	1
Distance from obstructions on roof (meters)	N/A	N/A	N/A	N/A
Distance from obstructions not on roof (meters)	N/A	N/A	N/A	N/A
Distance from trees (meters)	N/A	N/A	N/A	N/A

Distance to furnace or incinerator flue (meters)	52	52	52	52
Distance between collocated monitors (meters)	2	2	2	2
Unrestricted airflow (degrees)	360°	360°	360°	360°
Probe material for reactive gases (e.g. Pyrex, stainless steel, Teflon)	N/A	N/A	Stainless steel	Stainless steel
Residence time for reactive gases (seconds)	N/A	N/A	0.1	0.1
Will there be changes within the next 18 months? (Y/N)	No	No	No	No
Is it suitable for comparison against the annual PM2.5? (Y/N)	Yes	Yes	N/A	N/A
Frequency of flow rate verification for manual PM samplers	Monthly	Monthly	N/A	N/A
Frequency of flow rate verification for automated PM analyzers	N/A	N/A	N/A	N/A
Frequency of one-point QC check for gaseous instruments	N/A	N/A	Semi Annually	Semi Annually
Last Annual Performance Evaluation for gaseous parameters (MM/DD/YYYY)	N/A	N/A	10/15/13	10/15/13
Last two semi-annual flow rate audits for PM monitors (MM/DD/YYYY, MM/DD/YYYY)	06/28/2013, 12/20/2013	06/28/2013, 12/20/2013	N/A	N/A

Pollutant, POC	Metals, Cr6, Carbonyls, 4	Metals, Cr6, Carbonyls, 5	Polycyclic Aromatic Hydrocarbons, 1	
Parameter code	See Table 26	See Table 26	See Table 26	
Basic monitoring objective(s)	NAAQS	NAAQS	NAAQS	
Site type(s)	Population Exposure	Population Exposure	Population Exposure	
Monitor (type)	SLAMS/NATTS	SLAMS/NATTS/QA Collocated	SLAMS/NATTS	

Instrument manufacturer and model	RM Env. 924,A Sampler	RM Env. 924, B Sampler	Tisch PUF	
Method code	See Table 26	See Table 26	See Table 26	
FRM/FEM/ARM/ other	Other	Other	Other	
Collecting Agency	SCAQMD	SCAQMD	SCAQMD	
Analytical Lab (i.e. weigh lab, toxics lab, other)	SCAQMD	SCAQMD	SCAQMD	
Reporting Agency	SCAQMD	SCAQMD	ERG North Carolina	
Spatial scale (e.g. micro, neighborhood)	Urban	Urban	Urban	
Monitoring start date (MM/DD/YYYY)	01/2007	01/2007	01/2007	
Current sampling frequency (e.g. 1:3, continuous)	See Table 26	See Table 26	See Table 26	
Calculated sampling frequency (e.g. 1:3/1:1)	No CFR mandated sampling schedule.	No CFR mandated sampling schedule.	No CFR mandated sampling schedule.	
Sampling season (MM/DD-MM/DD)	01/01-12/31	01/01-12/31	01/01-12/31	
Probe height (meters)	12.18	12.18	12.18	
Distance from supporting structure (meters)	1.9	1.9	1.9	
Distance from obstructions on roof (meters)	N/A	N/A	Yes	
Distance from obstructions not on roof (meters)	N/A	N/A	N/A	
Distance from trees (meters)	N/A	N/A	N/A	
Distance to furnace or incinerator flue (meters)	52	52	52	
Distance between collocated monitors (meters)	2	2	N/A	
Unrestricted airflow (degrees)	360°	360°	360°	
Probe material for reactive gases (e.g. Pyrex, stainless steel, Teflon)	N/A	N/A	N/A	
Residence time for reactive gases (seconds)	N/A	N/A	N/A	
Will there be changes within the next 18 months? (Y/N)	No	No	No	

Is it suitable for comparison against the annual PM2.5? (Y/N)	N/A	N/A	N/A	
Frequency of flow rate verification for manual PM samplers	Monthly	Monthly	N/A	
Frequency of flow rate verification for automated PM analyzers	N/A	N/A	N/A	
Frequency of one-point QC check for gaseous instruments	N/A	N/A	N/A	
Last Annual Performance Evaluation for gaseous parameters (MM/DD/YYYY)	N/A	N/A	N/A	
Last two semi-annual flow rate audits for PM monitors (MM/DD/YYYY, MM/DD/YYYY)	N/A	N/A	N/A	

Pollutant, POC	Metals, Cr6, Carbonyls, N/A	VOCs, N/A	Carbonyls, 2	
Parameter code	N/A	N/A	See Table 26	
Basic monitoring objective(s)	NAAQS	NAAQS	NAAQS	
Site type(s)	Population Exposure	Population Exposure	Highest Concentration	
Monitor (type)	CA Air Toxics	CA Air Toxics	SLAMS/PAMS	
Instrument manufacturer and model	RM Env. 924	RM Env. 910PC	Atec 8000	
Method code	N/A	N/A	See Table 26	
FRM/FEM/ARM/ other	Other	Other	Other	
Collecting Agency	SCAQMD	SCAQMD	SCAQMD	
Analytical Lab (i.e. weigh lab, toxics lab, other)	ARB Toxics	ARB Toxics	SCAQMD	
Reporting Agency	ARB	ARB	SCAQMD	
Spatial scale (e.g. micro, neighborhood)	Neighborhood	Neighborhood	Neighborhood	
Monitoring start date (MM/DD/YYYY)	01/1989	01/1989	06/01/2009	

Current sampling frequency (e.g. 1:3, continuous)	1:12	1:12	1:6 or 1:1 Intensive PAMS	
Calculated sampling frequency (e.g. 1:3/1:1)	No CFR mandated sampling schedule.	No CFR mandated sampling schedule.	No CFR mandated sampling schedule.	
Sampling season (MM/DD-MM/DD)	01/01-12/31	01/01-12/31	01/01-12/31	
Probe height (meters)	12.18	12.6	12.3	
Distance from supporting structure (meters)	1.9	2.3	2	
Distance from obstructions on roof (meters)	N/A	N/A	N/A	
Distance from obstructions not on roof (meters)	N/A	N/A	N/A	
Distance from trees (meters)	N/A	N/A	N/A	
Distance to furnace or incinerator flue (meters)	52	52	52	
Distance between collocated monitors (meters)	2	2	N/A	
Unrestricted airflow (degrees)	360	360	360	
Probe material for reactive gases (e.g. Pyrex, stainless steel, Teflon)	N/A	Stainless steel	Stainless steel	
Residence time for reactive gases (seconds)	N/A	N/A	5.0	
Will there be changes within the next 18 months? (Y/N)	No	No	No	
Is it suitable for comparison against the annual PM _{2.5} ? (Y/N)	N/A	N/A	N/A	
Frequency of flow rate verification for manual PM samplers	N/A	N/A	N/A	
Frequency of flow rate verification for automated PM analyzers	N/A	N/A	N/A	
Frequency of one-point QC check for gaseous instruments	N/A	N/A	N/A	

Last Annual Performance Evaluation for gaseous parameters (MM/DD/YYYY)	N/A	N/A	N/A	
Last two semi-annual flow rate audits for PM monitors (MM/DD/YYYY, MM/DD/YYYY)	N/A	N/A	N/A	

Pollutant, POC	PM2.5 Carbon, N/A	PM2.5 Carbon, N/A	Speciated PM2.5, N/A	Speciated PM2.5, N/A
Parameter code	N/A	N/A	N/A	N/A
Basic monitoring objective(s)	NAAQS, Research Support	NAAQS, Research Support	NAAQS, Research Support	NAAQS, Research Support
Site type(s)	Population Exposure	Population Exposure	Population Exposure	Population Exposure
Monitor (type)	STN	STN /QA Collocated	STN	STN /QA Collocated
Instrument manufacturer and model	URG 3000, A Sampler	URG 3000, B Sampler	Met One SASS, A Sampler	Met One SASS, B Sampler
Method code	N/A	N/A	N/A	N/A
FRM/FEM/ARM/ other	Other	Other	Other	Other
Collecting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Analytical Lab (i.e. weigh lab, toxics lab, other)	EPA STN	EPA STN	EPA STN	EPA STN
Reporting Agency	EPA	EPA	EPA	EPA
Spatial scale (e.g. micro, neighborhood)	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Monitoring start date (MM/DD/YYYY)	03/07/2007	03/07/2007	03/2001	03/2001
Current sampling frequency (e.g. 1:3, continuous)	1:3	1:6	1:3	1:6
Calculated sampling frequency (e.g. 1:3/1:1)	1:3	1:3	1:3	1:3
Sampling season (MM/DD-MM/DD)	01/01-12/31	01/01-12/31	01/01-12/31	01/01-12/31
Probe height (meters)	12.3	12.3	12.0	12.0
Distance from supporting structure (meters)	2.0	2.0	1.8	1.8
Distance from obstructions on roof (meters)	N/A	N/A	N/A	N/A

Distance from obstructions not on roof (meters)	N/A	N/A	N/A	N/A
Distance from trees (meters)	N/A	N/A	N/A	N/A
Distance to furnace or incinerator flue (meters)	52	52	52	52
Distance between collocated monitors (meters)	2	2	2	2
Unrestricted airflow (degrees)	360°	360°	360°	360°
Probe material for reactive gases (e.g. Pyrex, stainless steel, Teflon)	N/A	N/A	N/A	N/A
Residence time for reactive gases (seconds)	N/A	N/A	N/A	N/A
Will there be changes within the next 18 months? (Y/N)	No	No	No	No
Is it suitable for comparison against the annual PM2.5? (Y/N)	N/A	N/A	N/A	N/A
Frequency of flow rate verification for manual PM samplers	Monthly	Monthly	Monthly	Monthly
Frequency of flow rate verification for automated PM analyzers	N/A	N/A	N/A	N/A
Frequency of one-point QC check for gaseous instruments	N/A	N/A	N/A	N/A
Last Annual Performance Evaluation for gaseous parameters (MM/DD/YYYY)	N/A	N/A	N/A	N/A
Last two semi-annual flow rate audits for PM monitors (MM/DD/YYYY, MM/DD/YYYY)	N/A	N/A	06/28/2013, 12/20/2013	06/28/2013, 12/20/2013

Pollutant, POC	Carbon Monoxide, 9	NOy, 9		
Parameter code	42101	42612		

Basic monitoring objective(s)	NAAQS	NAAQS		
Site type(s)	Population Exposure	Highest Concentration		
Monitor (type)	NCore	NCore		
Instrument manufacturer and model	Teledyne 300EU	Thermo 42i-Y		
Method code	593	574		
FRM/FEM/ARM/ other	FRM	N/A		
Collecting Agency	SCAQMD	SCAQMD		
Analytical Lab (i.e. weigh lab, toxics lab, other)	N/A	N/A		
Reporting Agency	SCAQMD	SCAQMD		
Spatial scale (e.g. micro, neighborhood)	Neighborhood	Neighborhood		
Monitoring start date (MM/DD/YYYY)	01/01/2011	01/01/2011		
Current sampling frequency (e.g. 1:3, continuous)	1:1	1:1		
Calculated sampling frequency (e.g. 1:3/1:1)	N/A	N/A		
Sampling season (MM/DD-MM/DD)	01/01-12/31	01/01-12/31		
Probe height (meters)	12.3	12.3		
Distance from supporting structure (meters)	2.0	2.0		
Distance from obstructions on roof (meters)	N/A	N/A		
Distance from obstructions not on roof (meters)	N/A	N/A		
Distance from trees (meters)	N/A	N/A		
Distance to furnace or incinerator flue (meters)	45	45		
Distance between collocated monitors (meters)	N/A	N/A		
Unrestricted airflow (degrees)	360°	360°		
Probe material for reactive gases (e.g. Pyrex, stainless steel, Teflon)	Teflon	Teflon		
Residence time for reactive gases (seconds)	N/A	N/A		

Will there be changes within the next 18 months? (Y/N)	No	No		
Is it suitable for comparison against the annual PM2.5? (Y/N)	No	No		
Frequency of flow rate verification for manual PM samplers	N/A	N/A		
Frequency of flow rate verification for automated PM analyzers	N/A	N/A		
Frequency of one-point QC check for gaseous instruments	Nightly	Nightly		
Last Annual Performance Evaluation for gaseous parameters (MM/DD/YYYY)	12/30/2013	12/30/2013		
Last two semi-annual flow rate audits for PM monitors (MM/DD/YYYY, MM/DD/YYYY)	N/A	N/A		

**Los Angeles-North Main Street
Site Photos**



Looking North from the probe.



Looking East from the probe.



Looking South from the probe.



Looking West from the probe.

**Los Angeles-North Main Street
Site Photos (Cont.)**



Looking at the probe from the North.



Looking at the probe from the East.



Looking at the probe from the South.



Looking at the probe from the West.

**Los Angeles-North Main Street
Site Photos**



Looking North from the probe.



Looking East from the probe.



Looking South from the probe.



Looking West from the probe.

**Los Angeles-North Main Street
Site Photos (Cont.)**



Looking at the probe from the North.



Looking at the probe from the East.



Looking at the probe from the South.



Looking at the probe from the West.